

MAINTENANCE Lighting

Flashlights



Bayco XPP-5422GMX features integrated magnets built into the bottom and handle.

Intrinsically Safe Flashlights

KEY	DESCRIPTION	COLOR	LIGHT TYPE	SIZE (INCH)	SETTINGS	LUMENS	DISTANCE (YARDS)	RUN TIME (HOURS)	BATTERY	RATINGS	SPECIAL FEATURES	STOCK #	EACH
A	Pelican™ StealthLite™ 2410 LED Flashlight	Yellow	LED	7 x 1.75	Spot	183	201	5.45	Four AA	Class I, II, III Div I, IPX7	—	33940	\$
B	Pelican StealthLite™ LED Flashlight	Black	LED	7 x 1.75	Spot	183	201	5.45	Four AA	Class I, II, III Div I, IPX7	—	33941	
C	Streamlight® Dualie® 3AA w/ Snag-Free Clip	Yellow	C4® LED	8.4 x 1.52	Spot/ Flood/ Dual	140 (Spot) 140 (Flood) 245 (Dual)	187 (Spot) 19 (Flood)	18 (Spot) 18 (Flood) 9 (Dual)	Three AA	Class I & II Div. 1, IPX7	—	94962	
D	Bayco® XPP-5420GX X-Series Safe Flashlight	Yellow	CREE® LED	7 x 1.8	Beam	210	204	14	Three AA (not included)	Class I, II, III Div. I, IP67	Built-in belt clip, removable lanyard, waterproof	330467	
E	Bayco XPP-5422GMX X-Series Dual-Mode Flashlight w/ Magnets	Yellow	CREE LED	7 x 1.8	Spot/ Flood/ Dual	210 (Spot) 130 (Flood) 285 (Dual)	185	14 (Spot) 20 (Flood) 10 (Dual)	Three AA (not included)	Class I, II, III Div. I, IP67	Magnet base, pocket clip, waterproof	330469	
F	Bayco XPP-5422GX X-Series Dual-Light Flashlight	Yellow	CREE LED	7 x 1.8	Spot/ Flood/ Dual	210 (Spot) 130 (Flood) 285 (Dual)	185	14 (Spot) 20 (Flood) 10 (Dual)	Three AA (not included)	Class I, II, III Div. I, IP67	Built-in belt clip, removable lanyard, waterproof	330468	
G	Pelican SabreLite™ 2010 LED Flashlight	Yellow	LED	8.25 x 1.75	Spot	129	147	22	Three C	Class I, II, III Div I, IPX7	—	33938	
H	Pelican SabreLite 2010 LED Flashlight	Black	LED	8.25 x 1.75	Spot	129	147	22	Three C	Class I, II, III Div I, IPX7	—	33939	
I	Streamlight HAZ-LO® Flashlight	Yellow	C4 LED	6.4 x .89	Spot	65	104	24	Two AA	Class I, II, III Div 2, IPX7	Pocket clip, wrist lanyard	94963	



Looking for

Safety Beacons & Lightbars

for your fleet vehicles? See pages 1543-1544.