

# TOOLS Concrete & Ductile Iron Pipe Cutting

## Wheeler-Rex Pipe Cutters

- "Snap" cutters for cast iron, soil pipe and concrete
- Ratchet or hydraulic operated



Wheeler-Rex chain type pipe cutters are made specifically for fast cutting of tile, cast iron and concrete pipe. The cutter chain is wrapped around the pipe and engaged in the cutter jaws, which are then actuated by either a ratchet wrench or a hydraulic pump. Chain cutters are not affected by dirt and sand and require a minimal amount of space.

Select the model you need based on the size and type of pipe you plan to cut. The **brown letter** displayed to the left of each model cutter also appears in the selection chart, which shows the cutting capabilities of each model. We have listed the most popular sizes used by the water industry. Hydraulic-actuated models are available with extended cutting capacities at extra cost.

**Note:** Chain type "snap" cutters are not capable of cutting ductile iron or steel pipe.

**Shipping:** Models 3890-12 and 5590-18 ship motor freight.

### Ratchet Operated Pipe Cutters

- Includes ratchet



DESCRIPTION	WT (LBS)	STOCK #	EACH
<b>A</b> 1/2-6" (37 to 150 mm) STD or 5" XH Soil Pipe; No-Hub & Tile	18	26110	\$
<b>B</b> 1/2-6" (37 to 150 mm) STD or 5" (125 mm) XH Soil Pipe; 8" (200 mm) No-Hub & Tile	19	25211	
<b>C</b> 1/2-6" (37 to 150 mm) STD or 5" (125 mm) XH Soil Pipe; 8" (200 mm) No-Hub & 10" (250 mm) Tile	20	25216	
<b>G</b> 1/2-6" (37 to 150 mm) STD or 5" (125 mm) XH Soil Pipe; 8" (200 mm) No-Hub & 12" (300 mm) Tile	22	25217	
<b>E</b> 1/2-6" (150 to 200 mm) STD or 5" (125 mm) XH Soil Pipe; 8" (200 mm) No-Hub & 15" (375 mm) Tile	23	25218	
Replacement Ratchet Wrench		25249	

### Model 3890-12

4 to 12" ASA Class 22 CI water main, 4 to 10" ASA Class 26 CI water main, and 4 to 12" STD and XH soil pipe, tile and concrete. Other models are available in the 3890 series for cutting larger diameters of soil pipe, tile and concrete up to 24". Comes complete with pump hose, case and initial fill of oil.



DESCRIPTION	STOCK #	EACH
<b>G</b> Model 3890-12	26071	\$

### Model 5590-18

6 to 18" ASA Class 22 & 26 CI water main, tile and concrete. Other models are available in the 5590 series for cutting Class 26 CI up to 20" and Class 22 CI, tile and concrete up to 36". Complete with pump, hose, case and initial fill of oil.



DESCRIPTION	STOCK #	EACH
<b>H</b> Model 5590-18	26072	\$

### Hydraulic Pipe Cutters Model 2990-6

2 to 6" ASA Class 22 CI water main, STD and XH soil pipe, and tile. Other models are available in the 2990 series for cutting larger diameters of soil pipe up to 8" and tile up to 15". Comes complete with pump, hose, case and initial fill of oil.



DESCRIPTION	STOCK #	EACH
<b>F</b> Model 2990-6	26070	\$

### We also RECOMMEND...

#### Hydroyl Hydraulic Pump Fluid

Wheeler-Rex hydraulic cutter guarantees are valid only when Hydroyl fluid is used.

DESCRIPTION	STOCK #	EACH
Hydroyl Fluid, Quart	26073	\$
Hydroyl Fluid, Gallon	26074	



### Recommended Cutting Capacities for Wheeler-Rex Pipe Cutters

Type of Pipe	Service Weight Cast Iron Soil Pipe	No-Hub Soil Pipe	Extra Heavy Cast Iron Soil	Tile (All Types)	Concrete	C.I. Water ASA Class 22 Reg. or Lined	C.I. Water ASA Class 25 Reg. or Lined	C.I. Water ASA Class 26 Reg. or Lined	Fly Ash	AC
1 1/2"	ABCDE	ABCDE	ABCDE	ABCDE						ABCDE
2"	ABCDEF	ABCDEF	ABCDEF	ABCDEF	F	F				ABCDE
3"	ABCDEF	ABCDEF	ABCDEF	ABCDEF	F	F				ABCDE
4"	ABCDEFG	ABCDEF	ABCDEFG	ABCDEF	F	FG	G	G	G	FG
6"	ABCDEFG	ABCDEF	GH	ABCDEF	FGH	FGH	GH	GH	G	FG
8"	GH	G	GH	BCDEG	GH	GH	GH	GH	H	GH
10"	GH	G	GH	CDEGH	GH	GH	GH	GH	H	GH
12"	GH	G	GH	DEGH	GH	GH	H	H	GH	GH
14"	H	H	EH	H	H	H	H	H		GH
15"	H	H	EH	H	H	H	H	H		GH
16"	H	H	H	H	H	H	H	H		H
18"	H	H	H	H	H	H	H	H		H