



Watts® Melt Blown Filter Cartridges

- Low cost with high dirt holding capacity
- Excellent chemical resistance

Melt blown cartridges are ideal for general filtration applications and are commonly used for reverse osmosis pre-filtration. The special polypropylene construction provides maximum filter life while eliminating media migration, channeling and unloading.

SIZE (OD x L)	MICRON	FLOW (GPM)	QTY/ CASE	STOCK #	CASE \$
2 1/2" x 9 7/8"	1	5	48	86835	\$
2 1/2" x 9 7/8"	5	6	48	86836	
2 1/2" x 9 7/8"	20	6	48	86837	
2 1/2" x 9 7/8"	50	9	48	86838	
<hr/>					
2 1/2" x 20"	1	6	12	86839	
2 1/2" x 20"	5	10	12	86840	
2 1/2" x 20"	20	12	12	86841	
2 1/2" x 20"	50	18	12	86842	
<hr/>					
4 1/2" x 9 7/8"	1	7	24	86843	
4 1/2" x 9 7/8"	5	7	24	86844	
4 1/2" x 9 7/8"	20	7	24	86845	
4 1/2" x 9 7/8"	50	7	24	86846	
<hr/>					
4 1/2" x 20"	1	9	12	86847	
4 1/2" x 20"	5	9	12	86848	
4 1/2" x 20"	20	9	12	86849	
4 1/2" x 20"	50	9	12	86850	



Claris® Melt-Blown Filter Cartridges

- Excellent filtration at high flow rates

These cartridges feature all polypropylene construction—no surfactants, binders or adhesives. Graded pore structure enhances dirt-holding capacity.

SIZE (OD x L)	MICRON	MAX FLOW (GPM)	QTY/ CASE	STOCK #	CASE \$
2 1/2" x 10"	1	5	36	90471	\$
2 1/2" x 10"	3	5	36	90484	
2 1/2" x 10"	5	5	36	90493	
2 1/2" x 10"	10	5	36	90466	
<hr/>					
2 1/2" x 10"	20	5	36	90476	
2 1/2" x 10"	30	5	36	90480	
2 1/2" x 10"	50	5	36	90488	
2 1/2" x 10"	75	5	36	90498	
<hr/>					
2 1/2" x 20"	1	10	24	90472	
2 1/2" x 20"	3	10	24	90485	
2 1/2" x 20"	5	10	24	90494	
2 1/2" x 20"	10	10	24	90467	
<hr/>					
2 1/2" x 20"	20	10	24	90477	
2 1/2" x 20"	30	10	24	90481	
2 1/2" x 20"	50	10	24	90489	
2 1/2" x 20"	75	10	24	90499	
<hr/>					
2 1/2" x 30"	1	15	12	90473	
2 1/2" x 30"	3	15	12	90486	
2 1/2" x 30"	5	15	12	90495	
2 1/2" x 30"	10	15	12	90468	
<hr/>					
2 1/2" x 30"	20	15	12	90478	
2 1/2" x 30"	30	15	12	90482	
2 1/2" x 30"	50	15	12	90490	
2 1/2" x 30"	75	15	12	90500	



USA BlueBook BRAND PRODUCTS

YOUR BEST VALUE!

USA BlueBook Jumbo Melt Blown Filter Cartridges

- 100% polypropylene—excellent chemical compatibility
- High dirt-holding capacity—reduces sediment, dirt and rust particles
- Comply with FDA requirements for food contact per CFR Title 21

Use these cartridges for efficient economical filtration. They feature 100% polypropylene construction, with no glues or additives. Maximum temperature: 140°F.



NSF/ANSI 61 by WQA



For use with: jumbo filter housings; see page 376.

SIZE (OD x L)	MICRON	FLOW (GPM)	STOCK #	EACH \$	QTY 4+ \$
7 3/4" x 9 5/8"	1	25	86899		
7 3/4" x 9 5/8"	5	25	86900		
7 3/4" x 9 5/8"	20	25	86902		
7 3/4" x 9 5/8"	50	25	86903		
7 3/4" x 9 5/8"	100	25	86904		
<hr/>					
7 3/4" x 19 1/2"	1	50	86905		
7 3/4" x 19 1/2"	5	50	86906		
7 3/4" x 19 1/2"	20	50	86908		
7 3/4" x 19 1/2"	50	50	86909		
7 3/4" x 19 1/2"	100	50	86910		
<hr/>					
7 3/4" x 30 3/4"	1	75	86911		
7 3/4" x 30 3/4"	5	75	86912		
7 3/4" x 30 3/4"	20	75	86914		
7 3/4" x 30 3/4"	50	75	86915		
7 3/4" x 30 3/4"	100	75	86916		

We also RECOMMEND...

Process Filter Differential Gauges

- Easily identify filter conditions
- Lead-free design suitable for use with potable water



This unique differential pressure gauge lets you know the state of an inline filter at a glance. A simple dial indicator displays status as one of three conditions: clean (green), change (yellow), or dirty (red). Pressure drop is determined on either side of the filter through 1/8" NPT(F) side process connections. Includes aluminum mounting base.

Accuracy:	±5% full scale
Wetted materials:	aluminum, SS, glass-filled nylon, fluoropolymer
Case materials:	glass-filled nylon, polyester, fluoroelastomer
Dial size:	2 1/2"
Operating temp:	200°F max
Max pressure:	300 psig

RANGE	CLEAN ZONE (GREEN)	CHANGE ZONE (YELLOW)	DIRTY ZONE (RED)	STOCK #	EACH \$
0 to 5 psid	0 to 2.5 psid	2.5 to 3.75 psid	3.75 to 5 psid	21120	\$
0 to 10 psid	0 to 5 psid	5 to 7.5 psid	7.5 to 10 psid	21128	
0 to 25 psid	0 to 11 psid	11 to 18.5 psid	18.5 to 25 psid	21164	