

PUMPS & PROCESS EQUIPMENT Centrifugal—Straight

Goolds MCC Series Cast Iron Centrifugal Pumps

- Cast-iron body with 316 stainless steel impeller
- Continuous-duty rated
- NSF-61 certified



UPDATED models!



Goolds MCC series end suction centrifugal pumps are of the highest quality available. The 316 SS impeller keeps the pump performing at maximum efficiency for the life of the pump. Casing can be rotated to nine different positions for various piping configurations.

Pumps listed here are configured with upgraded carbon/silicon carbide and Viton® seals, and are NSF-61 certified. Pick the pump that best suits your requirements based on desired flow and head (pressure).

Pump type:	straight centrifugal
Solids handling:	none, clear water only
Suction lift:	flooded suction required
Motor:	continuous-duty, 1/2 to 3 hp TEFC*, 5 hp ODP, 3500 rpm
Max working pressure:	75 psi
Max liquid temp:	212°F
Construction:	cast-iron casing, 316 stainless steel impeller, Viton elastomers
Seal:	mechanical, carbon/silicon carbide, Viton

MFR #	CURVE	HP	VOLTS	PHASE	STOCK #	EACH
100MC PUMPS, 1" OUTLET x 1 1/4" INLET						
100MC1D4E4	E	3/4	115/230	1	361451	\$
100MC1D5E4	E	3/4	208-230/460	3	361452	
100MC1E4D4	D	1	115/230	1	361453	
100MC1E5D4	D	1	208-230/460	3	361454	
100MC1F4C4	C	1 1/2	115/230	1	361455	
100MC1F5C4	C	1 1/2	208-230/460	3	361456	
100MC1G4B4	B	2	115/230	1	361457	
100MC1G5B4	B	2	208-230/460	3	361458	
100MC1H4A4	A	3	230	1	361459	
100MC1H5A4	A	3	208-230/460	3	361460	

125MC PUMPS, 1 1/4" OUTLET x 1 1/2" INLET						
125MC1F4J4	J	1 1/2	115/230	1	361461	\$
125MC1F5J4	J	1 1/2	208-230/460	3	361462	
125MC1F4H4	H	1 1/2	115/230	1	361463	
125MC1F5H4	H	1 1/2	208-230/460	3	361464	
125MC1G4G4	G	2	115/230	1	361465	
125MC1G5G4	G	2	208-230/460	3	361466	
125MC1H4F4	F	3	230	1	361467	
125MC1H5F4	F	3	208-230/460	3	361468	
125MC1H4E4	E	3	230	1	361469	
125MC1H5E4	E	3	208-230/460	3	361470	
125MC1J4D4	D	5*	230	1	361471	
125MC1J5D4	D	5*	208-230/460	3	361472	
125MC1J4C4	C	5*	230	1	361473	
125MC1J5C4	C	5*	208-230/460	3	361474	
125MC1J4B4	B	5*	230	1	361475	
125MC1J5B4	B	5*	208-230/460	3	361476	

150MC PUMPS, 1 1/2" OUTLET x 2" INLET						
150MC1F4G4	G	1 1/2	115/230	1	361477	\$
150MC1F5G4	G	1 1/2	208-230/460	3	361478	
150MC1G4F4	F	2	115/230	1	361479	
150MC1G5F4	F	2	208-230/460	3	361480	
150MC1H4E4	E	3	230	1	361481	
150MC1H5E4	E	3	208-230/460	3	361482	
150MC1H4D4	D	3	230	1	361483	
150MC1H5D4	D	3	208-230/460	3	361484	
150MC1J4C4	C	5*	230	1	361485	
150MC1J5C4	C	5*	208-230/460	3	361486	
150MC1J4B4	B	5*	230	1	361487	
150MC1J5B4	B	5*	208-230/460	3	361488	
150MC1J4A4	A	5*	230	1	361489	
150MC1J5A4	A	5*	208-230/460	3	361490	

*Pumps with 5-hp motors are only available in ODP.

