



Kupferle #95WM MainGuard Below-Grade Sampling Stations

- Extruded PVC construction; economical alternative to lead-free brass
- Adjustable locking horns for easy, flexible meter installation

Use the MainGuard #95WM sampling station to collect bacteriological samples at designated points directly from the main water line at any time, day or night. By using a sampling point outside of homes and businesses, you'll speed up sample collection time and reduce liability on private property.

This non-draining sampling station fits into any standard 5/8" x 3/4" meter box. It features a type I extruded PVC body and copper horns with brass meter nuts. Horns rotate for different angled installations, and are removable for easy replacement. Sampling station offers a brass spacing idler, isolation shut-off maintenance valve and a stainless steel threaded sampling point. The sampling rod (sold separately) includes a multi-directional swivel blow-off head and separate sampling bibb.

For a complete system, order a sampling station and sampling rod. The same sampling rod can be used at multiple stations. Optional rod case available.

MODEL	WATER METER SIZE	LAY LENGTH	STOCK #	EACH
#95WM	5/8" x 3/4"	7 1/2"	86246	\$

Accessories

DESCRIPTION	STOCK #	EACH
Sampling Rod, 36"	94298	\$
Optional Sampling Rod Carrying Case	94299	

Whirl-Pak® Thio-Bags

- Sterilized water and wastewater sampling bags

Thio-Bags contain enough sodium thiosulfate to neutralize chlorine at the time of collection. Purple closure tape makes these bags easy to identify. Bags have a convenient write-on strip to aid in sample identification. The 4-oz bags have a fill line at 100 mL and the 18-oz at 300 mL. EPA compliant for potable water sampling.



MFR #	SIZE	BAGS/BOX	STOCK #	BOX	QUANTITY
STANDARD THIO-BAGS					
B01040WA	4 oz (118 mL)	100	30920	\$	10+ Boxes
B01254WA	18 oz (532 mL)	100	30921	\$	24+ Boxes
STAND-UP THIO-BAGS					
B01402WA	4 oz (118 mL)	100	23231	\$	10+ Boxes
B01601WA	17 oz (500 mL)	100	23225	\$	10+ Boxes
B01603WA	34 oz (1000 mL)	100	23227	\$	10+ Boxes
B01604WA	68 oz (2000 mL)	100	23229	\$	10+ Boxes



Sampling station installs in place of water meter setting (meter sold separately).



94295

Kupferle #94WM MainGuard Below-Grade Sampling Stations

- Stations fit standard meter boxes
- Threaded sampling rod valve connection won't wear out



Includes protective cap

Use #94WM MainGuard sampling stations to collect samples from metered locations. Samples are drawn from the main side of the water supply, so they won't register water usage on the meter. By using a sampling point outside of homes and businesses, you'll speed up sample collection times and reduce liability on private property.

Stations feature all lead-free brass waterways and dual check valves with stainless steel sampling point. Portable sampling rod (sold separately) is threaded at the bottom, resulting in a positive-feel connection with the stations' spring-loaded receiving valve. This minimizes wear and tear, and reduces the chance for leakage over repeated uses. PVC cap protects valve connection when not in use.

For a complete system, order a sampling station and a sampling rod. Rod can be used at multiple stations. Optional rod case available. If replacing an existing meter, simply order a unit with the same connection size and lay length as your current meter.



MODEL	WATER METER SIZE	LAY LENGTH	STOCK #	EACH
#94WM	5/8" x 1/2"	7 1/2"	94294	\$
#94WM	5/8" x 3/4"	7 1/2"	94295	\$
#94WM	3/4" x 3/4"	9"	94296	\$
#94WM	1"	10 3/4"	94297	\$

Carrying case 94299 & sampling rod 94298 sold separately

Accessories

DESCRIPTION	STOCK #	EACH
Sampling Rod, 36"	94298	\$
Optional Sampling Rod Carrying Case	94299	



See pages 384-402 for **Water Meters.**