

VALVES Butterfly

Hayward® PVC Butterfly Valves



Great where corrosion is a concern

- Choose from manual or actuated models

Hayward PVC butterfly valves feature PVC construction with stainless steel shafts. They're great for water service, but also handle abrasive or slurry-type fluids. Choose from manual models with EPDM seals, or actuated models with EPDM, Viton® or FPM seals.

Other seals, operators, actuation options and voltages are available; contact USABlueBook for more information.

Shipping: Actuated valves 10" and larger ship motor freight.

| | |
|----------------------------|--|
| Valve construction: | PVC |
| Seal and seat: | EPDM, Viton or FPM |
| Disc: | PVC |
| Actuators: | HRSN series: 120 VAC, 60 Hz; NEMA 4/4X enclosure ECP series: 24V AC/DC; NEMA 4/4X enclosure |
| Max psi rating: | 150 psi |
| Temperature: | 120°F |
| Applications: | on/off service for fluids |
| Connections: | wafer |

A Manual Valves

- Available with lever or gear operators

Manual valves up to 8" feature lever handles with 19 lockable stop positions. 10" and 12" feature gear operators with handwheels.

| SIZE | # OF BOLTS | FACE TO FACE | OPERATOR | EPDM SEALS | |
|------|------------|--------------|----------|------------|------|
| | | | | STOCK # | EACH |
| 2" | 4 | 1.69" | Lever | 57965 | \$ |
| 3" | 4 | 1.81" | Lever | 57966 | |
| 4" | 8 | 2.06" | Lever | 57967 | |
| 6" | 8 | 2.19" | Lever | 57968 | |
| 8" | 8 | 2.38" | Lever | 57969 | |
| 10" | 12 | 2.69" | Gear | 57970 | |
| 12" | 12 | 3.06" | Gear | 57971 | |

B Actuated Valves with HRSN Actuators

- NEMA 4/4X rated enclosures

HRSN actuators feature a position indicator and two auxiliary limit switches. 6" and larger models also have a manual override shaft.

| SIZE | # OF BOLTS | FACE TO FACE | EPDM SEALS | | VITON SEALS | |
|--------|------------|--------------|------------|------|-------------|------|
| | | | STOCK # | EACH | STOCK # | EACH |
| 2" | 4 | 1.69" | 301746 | \$ | 301740 | \$ |
| 2 1/2" | 4 | 1.81" | 301747 | | 301741 | |
| 3" | 4 | 1.81" | 301748 | | 301742 | |
| 4" | 8 | 2.06" | 301749 | | 301743 | |
| 6" | 8 | 2.19" | 301750* | | 301744 | |
| 8" | 8 | 2.38" | 301751* | | 301745 | |
| 10" | 12 | 2.69" | 33589* | | — | — |
| 12" | 12 | 3.06" | 33590* | | — | — |

* Features manual override shaft.

C Actuated Valves with ECP Actuators

- NEMA 4/4X rated enclosures

ECP actuators feature a position indicator, four auxiliary limit switches, and GFPP (glass filled polypropylene) housing that provides superior corrosion resistance and performance in environments where most metal actuators cannot.

| SIZE | # OF BOLTS | FACE TO FACE | EPDM SEALS | | FPM SEALS | |
|--------|------------|--------------|------------|------|-----------|------|
| | | | STOCK # | EACH | STOCK # | EACH |
| 2" | 4 | 1.69" | 301757 | \$ | 301752 | \$ |
| 2 1/2" | 4 | 1.81" | 301758 | | 301753 | |
| 3" | 4 | 1.81" | 301759 | | 301754 | |
| 4" | 8 | 2.06" | 301760 | | 301755 | |
| 6" | 8 | 2.19" | 301761 | | 301756 | |



Manual Valve w/ Lever Handle (2 to 8" models)



Manual Valve w/ Handwheel (10" and 12" models)



HRSN Actuated Valve 301744



HRSN Actuated Valve 301740



ECP Actuated Valve 301752