

HOSE Discharge

Don't see the hose you need here? It's easy to order custom hose, and most ship within a few days. Call us for more information.

Red/Orange PVC Discharge Hose

- Heavy-duty premium hose ideal for pressure applications

Construction: PVC blend reinforced with three spiral plies of polyester. Mildew resistant.



SIZE, ID	MAX PSI*	50' M & F NPSM		50' NPT(M), F QUICK ALUM		50' M & F QUICK ALUM		50' M & F NST (FIRE HOSE THREAD)		HOSE ONLY, 25' (NO COUPLINGS)		HOSE ONLY, 50' (NO COUPLINGS)		HOSE ONLY, 100' (NO COUPLINGS)	
		STOCK #	EACH	STOCK #	EACH	STOCK #	EACH	STOCK #	EACH	STOCK #	EACH	STOCK #	EACH	STOCK #	EACH
1 1/2"	75-150	44216	\$	44226	\$	44236	\$	44217	\$	18450	\$	18455	\$	18460	\$
2"	75-150	44218		44228		44238		—	—	18451		18456		18461	
2 1/2"	50-150	44220		44230		44240		44221		18452		18457		18462	
3"	50-150	44222		44232		44242		—	—	18453		18458		18463	
4"	50-150	44224		44234		44244		—	—	18454		18459		18464	
6"	25-75	44225		—	—	44235		—	—	—		—		—	

*Max psi varies on hose assemblies. Please refer to our website for more information.

Yellow Jacket PVC/Nitrile Discharge Hose

- Heavy-duty premium hose ideal for use with high-pressure pumps and in irrigation applications

Construction: heavy PVC/nitrile blend reinforced with an extra heavy fabric.



SIZE, ID	MAX PSI*	50' M & F NPSM		50' NPT(M), F QUICK ALUM		50' M & F QUICK ALUM		HOSE ONLY, 25' (NO COUPLINGS)		HOSE ONLY, 50' (NO COUPLINGS)		HOSE ONLY, 100' (NO COUPLINGS)	
		STOCK #	EACH	STOCK #	EACH	STOCK #	EACH	STOCK #	EACH	STOCK #	EACH	STOCK #	EACH
1 1/2"	75-200	69447	\$	69444	\$	69445	\$	—	—	—	—	—	—
2"	75-200	69422		69427		69431		18465	\$	18470	\$	18475	\$
2 1/2"	50-200	69423		69428		69432		18466		18471		18476	
3"	50-200	69424		69429		69433		18467		18472		18477	
4"	50-75	69425		69430		69434		18468		18473		18478	
6"	25-75	69426		—	—	69435		18469		18474		18479	

*Max psi varies on hose assemblies. Please refer to our website for more information.

Urethane Water and Slurry Transfer Hose

- Ultra-rugged construction for applications requiring superior strength and abrasion resistance
- Blue NSF-61 grade hose available for use in potable water applications

Construction: highly abrasion-resistant extruded thermoplastic polyurethane (TPU) reinforced with high-strength circular-woven filament polyester yarn. Flexible at temperatures as low as -58°F. Choose from standard green hose or NSF-61 grade blue hose.



Standard Hose

SIZE, ID	MAX PSI*	50' M & F NPSM		50' M & F QUICK ALUM		50' M & F NST (FIRE HOSE THREAD)	
		STOCK #	EACH	STOCK #	EACH	STOCK #	EACH
STANDARD GREEN HOSE							
1 1/2"	215	78072	\$	78071	\$	17596	\$
2"	200-215	17597		17598		—	—
2 1/2"	150-200	78075		78074		17599	
3"	125-200	78078		78077		—	—
4"	100-170	78081		78080		—	—
NSF-61 GRADE BLUE HOSE							
1 1/2"	215	78054	\$	—	—	78053	\$
2 1/2"	215	78060		—	—	78059	

*Max psi varies on hose assemblies. Please refer to our website for more information.



Certified to NSF/ANSI 61



NSF-61 Grade Hose