

## Standard Series Hose Clamps

Band and housing are 300 Series stainless steel with 400 Series stainless steel hex screw.

### 5/16" Width with 1/4" Slotted Hex Screw

SIZE	CLAMP RANGE		STOCK #	EACH
	MIN	MAX		
4 SAE	7/32"	5/8"	44600	\$
8 SAE	7/16"	1"	44605	
16 SAE	11/16"	1 1/2"	44610	



### 1/2" Width with 5/16" Slotted Hex Screw

CLAMP RANGE				CLAMP RANGE			
MIN	MAX	STOCK #	EACH	MIN	MAX	STOCK #	EACH
7/16"	1"	44615	\$	2 13/16"	3 3/4"	44633	\$
9/16"	1 1/4"	44618		3 9/16"	4 1/2"	44636	
3/4"	1 3/4"	44621		4 1/16"	5"	44639	
15/16"	2 1/4"	44624		4 1/2"	6 1/2"	44642	
1 13/16"	2 3/4"	44627		5 3/4"	7 3/4"	44645	
2 1/16"	3"	44630					

## ABA Super Duty 316 SS Hose Clamps

- Corrosion-resistant 316 SS construction

Feature a smooth, non-perforated inside band surface with rolled edges to eliminate the risk of hose or tubing damage. Extra wide threads for engaging the worm gear tightening mechanism are stamped on the outside surface of the clamp. All sizes are 1/2" wide and have a 9/32" slotted hex screw.



OD RANGE	STOCK #	EACH	OD RANGE	STOCK #	EACH
1/2 to 13/16"	67812	\$	3 1/2 to 5"	67820	\$
5/8 to 15/16"	67813		4 1/2 to 6"	67821	
3/4 to 1 1/8"	67814		5 1/2 to 7"	67822	
7/8 to 1 1/4"	67815		6 1/2 to 8"	67823	
1 1/16 to 1 1/2"	67816		7 5/8 to 9 1/8"	67824	
1 1/4 to 2 1/4"	67817		8 5/8 to 10 1/8"	67825	
2 to 3"	67818		9 5/8 to 11 1/8"	67826	
2 3/4 to 3 3/4"	67819		10 5/8 to 12 1/8"	67827	

## Ratchet Torque Wrenches

Features fingertip control of reversing collar to tighten and loosen bolts without changing tools. Durable all-metal construction for years of dependable use with all banded products. 5/16" size is preset to 60 lbs of torque; 3/8" size to 80 lbs.



DESCRIPTION	STOCK #	EACH
5/16" Wrench	44790	\$
3/8" Wrench	44791	

## Flexible Clamp Drivers

This tool can tighten clamps in positions as difficult as 90°. 9/32" socket maintains a steady grip on the screw and prevents the driver from slipping.



DESCRIPTION	STOCK #	EACH
Flexible Clamp Driver	67828	\$

## Hose Menders

- Unplated steel

HOSE, ID	STOCK #	EACH
1"	60591	\$
1 1/2"	60592	
2"	60594	
2 1/2"	60595	
3"	60596	
4"	60597	
6"	60598	

## Lead-Free Hose and Hydrant Adapters



- Color coded blue for potable water

These lead-free aluminum adapters feature an infused oxide coating that penetrates the aluminum surface for a harder, more durable finish.



INLET/OUTLET SIZE	STOCK #	EACH
<b>FEMALE x MALE ADAPTERS</b>		
1 1/2" NST x 1 1/2" NPT	52516	\$
2 1/2" NST x 3/4" GHT	52517	
2 1/2" NST x 3/4" NPT	52518	
2 1/2" NST x 1" NPT	52519	
2 1/2" NST x 1 1/2" NPT	52520	
2 1/2" NST x 1 1/2" NST	52521	
2 1/2" NST x 2" NPT	52522	
2 1/2" NST x 2 1/2" NPT	52523	
4" NST x 2 1/2" NPT	52524	
4 1/2" NST x 2 1/2" NPT	52525	



<b>FEMALE x MALE SWIVEL ADAPTERS</b>		
1 1/2" NST x 1 1/2" NPT	52526	\$
2 1/2" NST x 1 1/2" NPT	52527	
2 1/2" NST x 2" NPT	52528	
2 1/2" NST x 2 1/2" NPT	52529	
<b>MALE x MALE ADAPTERS</b>		
1 1/2" NST x 1 1/2" NPT	52530	\$
2 1/2" NST x 1" NPT	52531	
2 1/2" NST x 1 1/2" NPT	52532	
2 1/2" NST x 2" NPT	52533	
2 1/2" NST x 2 1/2" NPT	52534	

## Band-It Tools

When replacing couplings on a hose end, wrap the banding around the hose and tighten them with the Band-It tool. Use buckles to lock the band in place.



DESCRIPTION	STOCK #	EACH
Band-It Tool	44351	\$

### Banding & Buckles

WIDTH	STOCK #	BOX
<b>201 SS BANDING, 100 FT/BOX</b>		
1/2"	44353	\$
5/8"	44355	
3/4"	44357	
<b>201 SS BUCKLES, 100/BOX</b>		
1/2"	44107	\$
5/8"	44109	
3/4"	44111	



## Create-A-Clamp Kits

Make sure you always have the right length clamp on hand for everyday repairs. Simply cut the length of banding you need from a reel, attach the worm drive assembly to the two ends, and you're ready to go. 1/2" wide banding is made of 300 series stainless steel and the housing is 9/16" 410 stainless steel.

**Includes:** 50'L x 1/2"W band and 20 fasteners with 5/16" slotted hex screw.

DESCRIPTION	STOCK #	EACH
Create-A-Clamp Kit	17208	\$

